

6" CLASSIC WALL PANEL ENGINEERED RECYCLED RIGID PVC



TESTING

- CLASS A FIRE RATED
- ICCES-ESR
- ASTM D3679-17
- ASTM E119-22
- ASTM G154-16
- ASTM G155-21
- ASTM D635-18
- ASTM E330/E330-14
- NFPA285-19
- NFPA268-17
- AAMA 303-19
- AAMA 307-16
- AAMA 664-21
- MIAMI DADE COUNTY, NOA. 23-1215.02
- TAS 202
- TAS 203
- TDI EC-149
- FLORIDA FL45923-R1 (DBPR)
- WILDLAND URBAN INTERFACE 8140-2381:0001 (WUI)

Finishes

WOODGRAINS, SOLID COLORS, BRUSHED METALLICS, ANODIZED & INTERIOR FINISHES
NON-STOCK COLORS AVAILABLE (ADDITIONAL LEAD TIMES)

1/2" EXTERIOR WALL PANEL

6" - 12', 16', 20' & 30'
CUSTOM LENGTHS AVAILABLE.
Please Note: if you are using our classic wall 1/2" panel for soffit ventilation is supplied by others.

ALUMINUM /PVC TRIMS

2PC OUTSIDE CORNER (2" & 3.5"), 2PC J-TRIM (2" & 3.5"), 2PC ALUMINUM H-TRIM (2.75"), 1PC PVC INSIDE CORNER, STARTER STRIP

LEAD TIMES

1-2 WEEK LEAD TIME FOR STOCK COLORS + SHIPPING
2-3 WEEKS FOR NON-STOCK COLORS + SHIPPING

CHAMCLAD ADVANTAGE

- 50 YEAR WARRANTY (15 YEAR NON-PRORATED)
- CONTRIBUTES TO LEED CERTIFICATION
- SCRATCH & GRAFFITI RESISTANT
- SUPERIOR UV PROTECTION
- IMPERVIOUS TO WATER ABSORPTION, BACTERIA AND MOLD
- LOW MAINTENANCE
- HIGH IMPACT RESISTANCE
- SHORT LEAD TIMES
- CANADIAN MANUFACTURED FROM 100% RECYCLED RIGID PVC
- CANADA AND US DISTRIBUTION
- MAY BE USED ON INTERIOR APPLICATIONS

